



Conservation roof window

The contemporary choice for traditional properties

The Conservation roof window is the perfect combination of the past and present. The window's black exterior profile and glazing bar blend seamlessly into the roof to match the building's original characteristics.

Its additional features offer you the same convenience as a standard VELUX roof window.


- Traditional external appearance
- Centre-pivot option for easy operation
- Top-hung option for uninterrupted panoramic views
- Top control bar with integrated ventilation
- Fresh air even when the window is closed
- Pivot function for easy cleaning

Roof pitch

Centre-pivot, top operated



Top-hung, bottom operated



The window is suitable for roof pitches between 13°-55°, also suitable for roof pitches between 55° and 75° with special springs

Interior finish options



White painted
Bright white finish for modern interiors

Glazing options

	Rain noise reduction		Safety lamination		Toughened glass		UV filter		Easy-to-clean		Anti-dew
	✓		✓		✓		✓				

Double glazing
--70

Thermal transmittance of glazing (U_g-value)

1.0

Read more about glazing specifications on page 22.

Blinds and shutters

- Consider interior blinds for light control, and anti-heat blinds or shutters for added heat protection

Read more on page 121.



External frame sizes (w x h) cm

U _w -value	CK04	CK06	FK06	MK06	MK08	UK04
W/m ² K	55x98	66x118	78x140	78x140	134x98	

Centre-pivot white painted

GGL SD5N2	GGL 2570 roof window + EDN recessed flashing for slate up to 8 mm thick (min 20°)	1.3	605	629	694	733	791	919
GGL SL5P01	GGL 2570 roof window + EDP flashing for plain tiles up to 14 mm thick (min 25°)	1.3	543	564	627	662	716	834
GGL SJ5W01	GGL 2570 roof window + EDW flashing for tiles up to 120 mm in profile (min 13°)	1.3	543	564	627	662	716	834
GGL SD5J2	GGL 2570 roof window + EDJ recessed flashing for tiles up to 90 mm in profile (min 20°)	1.3	605	629	694	733	791	919

Top-hung white painted

GPL SD5N2	GPL 2570 roof window + EDN recessed flashing for slate up to 8 mm thick (min 20°)	1.3	-	-	-	-	961	-
GPL SL5P01	GPL 2570 roof window + EDP flashing for plain tiles up to 14 mm thick (min 25°)	1.3	-	-	-	-	886	-
GPL SJ5W01	GPL 2570 roof window + EDW flashing for tiles up to 120 mm in profile (min 15°)	1.3	-	-	-	-	886	-
GPL SD5J2	GPL 2570 roof window + EDJ recessed flashing for tiles up to 90 mm in profile (min 20°)	1.3	-	-	-	-	961	-

All prices in GBP (£)
Find all sizes and prices on velux.co.uk