

Front:

Page 23

4019

EXISTING DOORWAY
FROM HOUSE TO
SCREENED IN.

EGFUBLAUWY
JDN EUCSD
IN CONCLFE
BELOW LC SUB

00

iii

١٥

 $\frac{1}{2}$

- CURE CAVITIES USING AVALOK/THERMATEX OR SA INSULATED PPS TO DOOR/WINDOW REVEALS TO UNIT/PRECAST DETESTAL AIR LOSS OR AS DCL
- PROVIDE STAINLESS STEEL CAVITY WASHES @ 750% #12, 450% VIT BEDDED FROM INTO EACH LEAK TO SLOPE OUTWARDS WITH EXTRACTIVES TO DOOR/WINDOW REVEALS @ 225%
- GROUND CONDITIONS/SPECIFIC EXISTING FOUNDATIONS DICTATE THAT AN EXPANSION/MOVEMENT JOINT BE CREATED WHERE NEW BRICK/BLOCK CANTY WALL MASQUERADE ABOUTS FIRE AND A STAINLESS STEEL PREPAREDLY SUPPLY SYSTEM FITTED AND A 12m GAP FILLER WITH FLEXIBLE OR SA EXPANSION BOARD AND A COURED MASTIC JOINT SEAMANT TO SEAL EXTERMINAL ETC.