

Hydropave Pedesta


SCAN HERE

Versatile permeable paving.

Hydropave Pedesta has a smooth surface and a timeless appeal. Available in four colours, this paving provides you with plenty of scope to create patterns and designs.

- Functions as a SuDS paving system
- Superb hard-wearing smooth surface
- Vibrant long-lasting colours



200 x 100mm

Sizes


60mm
80mm

Depths

 **PrimeTop®**  **Ef-Stop®**


Finish


Pedestrian
Use



Light
Traffic



Commercial
Traffic



BIM
Level 2

Refer to relevant guidance in BS 7533



Hydropave Pedesta



Specification

 **PrimeTop®**  **Ef-Stop®**

Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Surface Layer	Hard-wearing surface layer with a minimum layer of 4mm and >350kgs/m ³ cement
Surface Finish	Smooth
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Frost Protection	Yes
Drainage Void Width	5.5% to accommodate correct grit grading, reduce maintenance and maximise drainage flow rate
Strength	Typical tensile splitting strength of >3.6MPa
Slip/Skid risk	Extremely Low
Installed to	BS 7533-3:2005
BS	Plus Q24 115 Create 45-20-64/400 Plus Q24 117 Create 45-20-64/400 Plus Q24 119 Create 45-20-64/400
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance	Class 3
Durability (Freeze-thaw)	Class 3
External Fire Performance	Deemed to satisfy. See Commission Decision 2000/553/EC
Reaction to fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 12%
Carbon Footprint	60mm 14.17kgCo ² e/m ² 80mm 20.98kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breem rating www.bre.co.uk	60mm:A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base. 80mm:B , according to the Green Guide to Specification, 4 th Edition 2009. A , can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk

Hydropave Pedesta



Stock

product	size (mm)	colours available	edge	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Hydropave Pedesta BIM	200 x 100 x 60	Bracken, Brindle, Charcoal, Natural	Chamfer	YES	13.44	2.24	50	672	1808	1798
	200 x 100 x 80	Bracken, Brindle, Charcoal, Natural	Pencil chamfer	YES	9.6	1.6	50	480	1732	1722

BIM - This product is available to download from our website in BIM Level 2 format.

Bracken



Brindle



Charcoal



Natural



Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

[tobermore.co.uk](https://www.tobermore.co.uk)