

MUB 042 500EV sileo Multibox

Centrifugal box fan, insulated, flexible outlet


Item Number: [235406](#)

Variant: 230V 1~ 50Hz - 90° air flow

- Speed-controllable
- Modular system
- Integral thermal contacts
- Low sound level
- Flexible airflow direction due to removable panels
- Installation in any mounting position
- Maintenance-free and reliable

The MUB fans size 500 have 3D profiled impellers with backward curved blades, manufactured from polyamide. The MUB 500 is equipped with external rotor motors, fully speed controllable. For speed controlling with a frequency converter a type with all pole sine filter is needed!. The three phase motors are D/Y connected for two speed operation. Motor protection is done by thermal contacts, which have to be connected to an external motor protection device. The casing consists of a corrosion-resistant aluminium frame with fibreglass reinforced plastic corners of PA6; highly shock-resistant.

The double skin panels are manufactured from galvanised steel with 30 mm mineral wool insulation. To avoid condensation the profile is provided with a separate chamber to fix screws. The Multibox fans are delivered for straight through airflow but can easily be rebuilt due to removable panels. This allows flexible ventilation solutions. The MUB can also be used as extract- or supply air unit in air handling units. Installation in any mounting position is possible.



MUB with additional modules (filters, heaters etc.) are available as air handling units "K025, K042 or K062" on request!


Technical parameters

Nominal data		
Voltage (nominal)	230	V
Frequency	50	Hz
Phases	1~	
Input power	1,130	W
Input current	5.56	A
Impeller speed	1,388	rpm
Air flow	max 2.088	m³/s
Capacitance of capacitor	30	µF
Temperature of transported air	max 60	°C
Max temperature of transported air, when speed controlled	60	°C

Protection/Classification	
Enclosure class, motor	IP54
Insulation class	F
Data according to ErP	
ErP ready	ErP 2018
Dimensions and weights	
Weight	61 kg
Others	
Motor type	AC

Performance

Performance curve



Hydraulic data


Required air flow	1.70 m³/s
Required static pressure	199 Pa
Working air flow	1.71 m³/s
Working static pressure	200 Pa
Air density	1.204 kg/m³
Power	1133.4 W
Fan control - RPM	1387 rpm
Current	5.60 A
SFP	0.664 kW/m³/s
Control voltage	230.0 V
Supply voltage	230 V

Sound power level		63	125	250	500	1k	2k	4k	8k	Total
Inlet	dB(A)	48	67	69	75	79	78	74	66	83
Outlet	dB(A)	49	68	71	76	80	79	76	67	85
Surrounding	dB(A)	27	48	45	45	50	52	42	31	56
Sound pressure level at 3m (20m² Sabine)	dB(A)	-	-	-	-	-	-	-	-	49
Sound pressure level at 3m free field	dB(A)	-	-	-	-	-	-	-	-	35

Accessories


Dimension

MUB 042	□A	□B	□C	□D	E
400/450/500	690	690	590	548	21



Wiring

230V 1~



Acoustic

The Level of Casing-Breakout-Noise depends on the quality of shielding the acoustic inlet and outlet noises.

The shown Level of Casing-Breakout-Noise will be reached only in case of 100 % shielding the acoustic inlet and outlet noise and a correspondingly low environment noise.

Product			
Trade name		Systemair	
Product name		MUB 042 500E4	
Ecodesign			
ErP compliance		2018	
Unit category		NRVU	
Drive		External MSD or VSD	
Unit type		UVU	
Heat recovery type		None	
Temperature ratio (UVU)		Not applicable	
qv nom		1.15	m³/s
P nom		1.054	kW
Ps nom		373	Pa
Fan efficiency		40.6	%
External Leakage		5	%
Sound power (LWA)		83	dB(A)

Accessories

- FGV 042/586-586 flex. conn. (4605)
- Motor protect. switch S-ET 10 (161199)
- REV-5POL/05-7,5kW R/Y (33979)
- SD-MUB Vibration pad set (37324)
- UGS 042/500 adapter flex. (4357)
- WSG 042 MUB complete (31485)
- CCM inlet MUB042 d400 (311780)
- CCM outlet MUB042 d400 (311682)
- CCMI outlet 042 d400 KIT 30mm (239093)
- GRU 042-690/100 (276661)
- KKC-DX-R 042 cooling section (277265)
- KKC-W-R 042 cooling section (277273)
- KKH-HW 042 heater-section (93339)
- Frequency converter FRQ5SE-6A (37421)
- REU 7 Speed control (5007)
- RTRE 7 Speed control (5011)
- TUNE-AHU-DE007-042-588x588-M0 (79881)
- WSD 042 (730x730x70) complete (31481)
- Frequency converter FRQSE-6A (37419)
- CCM inlet MUB042 d500 (311781)
- CCM outlet MUB042 d500 (311683)
- CCMI outlet 042 d500 KIT 30mm (239094)
- KKC-DX-L 042 cooling section (277261)
- KKC-W-L 042 cooling section (277269)
- KKF 30 042-filter-section (93311)
- KKS 042 silencer-section (276851)

Documents

- Installation, Operation and Maintenance instruction_001
- UKCA DECLARATION OF CONFORMITY_MUB_EN_002.PDF
- COMMISSIONING REPORT_FANS_160628_EN_001.PDF