

AS DETAIL (A)(4)

- PROVIDE A PREPARED 'STAINLESS-STEEL' "POSSIBLE-TIE" SYSTEM. IN USE OF ATTEMPTING TO TIGHTEN BOND OR SUBJECTED TO EXISTING MASONRY AND CHANGED TO SUIT COURSE OF NEW MASONRY TO ENSURE A SECURE, ROBUST & POSITIVE CONNECTION OF NEW MASONRY TO EXISTING.
- LINTER'S:- USE CATHODIC CORROSION RESISTANT COATED BARS, 100% GALVANIZED STEEL INTER UNITS OR SA, AS DETAILS (A), (C) & (G) ONTO MIN 150mm DEEPENINGS, TO SUIT SPAN, CATCH UNITS etc AND ALSO BE ENCASED IN PINK-12HR CYPROX. FIRE LINE RD AS DORBL etc
- EARLY WARNING SYSTEM

• Position of stud wall between BEDD & BATHS TO BE ADJUSTED TO SUIT ON SITE TO SUITE.

15+ FLOOR AREA'S M²

up

BED ①	2.1 × 6.4	13.44
SUITE	2.25 × 2.1	4.72
		<u>18.17 M²</u>

"

SED 1st. FLOOR. PLAN

ADEN

DRGN

8

