

PRESTO



INSTALLATION GUIDE

■ **simplified**



GEOWEB® Tree Root Protection






GEOWEB® Tree Root Protection


- 1 Prepare subgrade. Remove debris, rocks.




- 2 Install TRP4000 geotextile. Overlaps by minimum 300 mm.





- 3 Partially expand GEOWEB® sections.




- 4 Connect GEOWEB® sections with ATRA® keys.



- 5 Connect side to side (A) and end to end (B).



- 6 Fully expand GEOWEB® sections.



IMPORTANT NOTE:


The simplified installation guide provided by Presto GEOSYSTEMS® is intended as a general guideline only. The contractor should follow contract plans and specifications and refer to detailed installation guidelines for more information.

- 7** Hold sections open. Use Options A, B, C or D.

A T-Bars



B ATRA® anchors




C Wood Stakes



D Infill Select Cells




- 8** Infill GEOWEB® cells.




- 9** Spread Infill ensuring a 25 mm overfill at all times.



- 10** If required, use a 4t smooth, non-vibrating roller on overfilled GEOWEB® system. Refill as needed to ensure a 25 mm overfill.



- 11** Surface option ready to install according to specification.



Greenfix
Soil Stabilisation and Erosion Control Specialists

info@greenfix.co.uk
tel: 01608 666027
www.greenfix.co.uk

Geoweb infill material for Tree Root Protection
Clean Angular Stone 4-20mm

Specification for open graded infill material for Geoweb cellular confinement within tree root protection applications. The no fines material is to ensure high ratio void space which corresponds with ideal soil void ratios for tree root health.

Material to BS EN1342 or BS EN12620. Crushed gravel is not permitted.

Properties of material	Test	Value
Grading of particle size	BS EN 13242	Grading 4-20mm
Fines Content	BS EN 13242	f ₈₀
Shape flatness index	BS EN 13242	F ₈₀
Resistance to fragmentation	BS EN 13242	LA ₁₀
Resistance to wear	BS EN 13242	M ₁₀ 20
Water absorption rate BS EN 1097-6:2000 clause 7	BS EN 13242	WA ₂ 2
For typical WA > 2% magnesium sulphate soundness	BS EN 13242	MS ₁₈
Acid soluble sulphate content air-cooled blast furnace slag	BS EN 13242	ASo ₁
Acid soluble sulphate content non air cooled blast furnace slag	BS EN 13242	ASo ₂
Total sulphur aggregates other than air cooled blast furnace slag	BS EN 13242	<1% by mass
Total sulphur air cooled blast furnace slag	BS EN 13242	<2% by mass

Sieve Size mm	Percentage of 4-20mm passing
40	100
31.5	98 - 100
20	90 - 99
10	25 - 70
4	0 - 15
2	0 - 5
1	-

Air cooled blast furnace and steel slag should be free from Dicalcium silicate and iron disintegration in accordance with BS EN 13242:2002, 6.4.2.2 v5
Leaching of materials for blast furnace slag and other recycled materials should meet requirements of the Environmental waste acceptance criteria for inert waste when tested in accordance with BS EN 12457-3
On poor site conditions which require compaction, this should be minimum 4 passes of a smooth wheeled roller at max weight 1000kg/m width without vibration.

For assistance on correct 4–20mm clean angular stone infill specification, please contact Greenfix technical team.

MATERIALS SUPPLIED BY **Greenfix**

GEOWEB®



TRP4000
Non-woven Geotextile



ANCHORS



ATRA® KEY



ADDITIONAL MATERIALS REQUIRED

4–20mm clean, angular stone



LIMITED WARRANTY

Presto GEOSYSTEMS® warrants each GEOWEB® section which it ships to be free from defects in materials and workmanship at the time of manufacture. Presto's exclusive liability under this warranty or otherwise will be to furnish without charge to Presto's customer at the original f.o.b. point a replacement for any section which proves to be defective under normal use and service during the 10-year period which begins on the date of shipment by Presto. Presto reserves the right to inspect any allegedly defective section in order to verify the defect and ascertain its cause.

This warranty does not cover defects attributable to causes or occurrences beyond Presto's control and unrelated to the manufacturing process, including, but not limited to, abuse, misuse, mishandling, neglect, improper storage, improper installation, improper alteration or improper application.

PRESTO MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, WRITTEN OR ORAL, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OR MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE, IN CONNECTION WITH THE GEOWEB® SYSTEM. IN NO EVENT SHALL PRESTO BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR THE BREACH OF ANY EXPRESS OR IMPLIED WARRANTY OR FOR ANY OTHER REASON, INCLUDING NEGLIGENCE, IN CONNECTION WITH THE GEOWEB® SYSTEM.

GEOSYSTEMS®, GEOWEB®, and ATRA® are registered trademarks of Reynolds Presto Products Inc.

GEOWEB® MANUFACTURER:



PRESTO GEOSYSTEMS®
Appleton, Wisconsin, USA

EU HEAD OFFICE/ENGINEERING SUPPORT:



SOILTEC GmbH: Germany
www.soiltec-geosystems.de

DISTRIBUTED BY:



Greenfix Soil Stabilisation & Erosion Control Limited
Old Manor Farm Yard
Beckford Road
Ashton under Hill
Evesham
Worcestershire
WR11 7SU
info@greenfix.co.uk
www.greenfix.co.uk
01608666027