




AAZTEC LED

Asymmetrical



- High performance die-cast aluminium LED floodlight suitable for industrial applications
- High output, high efficiency asymmetric lens technology for anti-light pollution
- Pre-installed breathable gland prevents internal moisture accumulation
- Bracket design allows installation without removing mounting bracket
- High efficiency up to 143 Lm/W
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation
- Non-dimmable



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-30°C to 50°C	L80 54,000	70	5	60°x120°	1	IP66	IK08

CODE	DESCRIPTION	WATTAGE	CCY	LUMENS	LM/W	A	B	C	WINDAGE
AAZLED50/ASY	Daylight	50W	5000K	6800lm	136lm	267mm	190mm	55mm	0.07
AAZLED100/ASY		100W		14000lm	143lm	314mm	230mm	61mm	0.09
AAZLED150/ASY		150W		21000lm	141lm	360mm	260mm	67mm	0.11
AAZLED200/ASY		200W		28000lm	141lm	398mm	300mm	70mm	0.14
AAZLED300/ASY		300W		43000lm	142lm	470mm	363mm	80mm	0.2

CODE (OPTIONS)	DESCRIPTION
/PC	Electronic Photocell

CODE (ACCESSORIES)	DESCRIPTION
AAZLED/60PMA	60mm Pole Mount Adaptor
AAZLED/76PMA	76mm Pole Mount Adaptor

CODE (ACCESSORIES)	DESCRIPTION
AAZLED/40-90PCA	40-90mm Pole Clamp Accessory 50-150W
AAZLED/40-150PCA	40-150mm Pole Clamp Accessory 200W-300W