



- $$\underline{\underline{\text{Total} = 27.24 \text{ m}^2}}$$

DRG 10

1. EARLY WARNING SYSTEM.

- AS B. REAS DOLB PARA 1.1 to 1.24 PROVIDE A SERIES OF GENUINE MONITOR AUTOMATED + INTERLINKED SMOKE/HEAT DETECTOR ALARMS TO GIVE EARLY WARNING OF HEAT, SMOKE AND FLAME AS FOLLOWS. WARMING OF HEAT, SMOKE AND FLAME AS FOLLOWS. LOCATED TO HALLWAY @ BOTTOM OF STAIRS, LANDING & TOP OF STAIRS ON 1st floor with an additional unit located top of stairs to lobby - induction HOB TO OPEN PLAN G/F APARTMENT TO COOKER - induction HOB TO OPEN PLAN G/F KITCHEN AREA AND ADDITIONAL ADPT 4 F STUDY AREA.....
- UNITS TO BE INSTALLED TO 5039 PT 1 TO BE SEPARATELY RISE AND MAINS WIRING TO POWER SUPPLIES AND ALARMED WITHIN 3m of 1st floor BEDROOM DOORS
- AS GARDEN SPEC/NEST PRACTICE. ADVISE SITE SPECIFIC MEANS OF ESCAPE WINDUWS TO WARTHOUSE REPAIR AS B. REAS DOLB para 2.8 (a)

1. 5.1 SUITE: CREATE AN 1st SUITE FACILITY off 1st floor MASTER BED @ FRONT MIN 1m INDEX WITH OF EXIT TO PORCH IN A WC, WITH SHOWER UNIT TO A REAR DOOR ON SITE, SCHEDULES OF WORKS FOR HOT AND COLD WATER SUPPLIES, FURNITURE DISCHARGE TO MAINAGE TO BS 5572:1978. EXTENSION TO AS DOOR FRAME) AND AN OPEN DOOR/DOUBLE GLAZED WINDOW TO FRONT FOR PRIVATE PURCHASES.

- REMOVE EXISTING TO OLD BED @ M/T REPAIRS/FLOOR AND ERECT A MIN 900 STAY BAUSTED GUARDRAIL UP OFF FLOOR AS DOCK. D/A 4M 11 ETC, BUILD STONE INSULATED JUST TO REINFORCED PARTITION TO NEW POSITION TO BED @ TO AUDITORIUM MIN 900mm EXISTING LANDING AND FROM AN EXISTING OPENING IN DECK, CAPSULE AND INTERPOSED 1st floor BED @ M/T TO FLOOR REPAIRS AND INST 2x 150x100 PC UNITS OFF TO SUITE INT DOOR AND FRAME.
- REPAIR EXISTING WINDOW AND BUILD UP FLOOR ETC.

1. STAIR PARTITION WALLS: UNLESS STATED OTHERWISE TO BE SET OUT/ARRANGED AS PROPOSED FLOOR PLANS IN EX-150x505mm STUD FRAMEWORK. HORIZONTALS OF 150x505mm STUD FRAMEWORK. VERTICAL STAIRS @ 400x100mm STUDS TO SUIT WITH 50mm, 10kg/m³ DENSE GROUT UNDER SAND INSULATION BETWEEN STAIRS AS DOOR E2 WITH 12.5mm GYP DOW BASED PASTER REPAIRS (FILL-PAKED TO SUITE) TO MEET MINIMUM EUROPEAN STANDARD AS DOOR TABULE 4.1 FOR 3/4mm SKIN IT AND 2CT-EMULSION DECOR AND/OR SPECIALLY CHARGED CEAMICS TO SUITE AS SPECIFIED ON SITE ETC