

MATCHING 102mm BUTTER LEAF, STEEL-SMOTHER CAPPED FACE BRICKS IN 1:3 CEMENT MORTAR. STATIONARY BONDING WITH DOOR  
 ON SOLE SOLDER BANDS OVER UNITS TO DOOR/WINDOWS AS DETAILS D, E, F, G, H etc WITH CONCEALED BUTTER LEAF  
 POINTING AS EXC - A 100mm 3:5 NUGTUBUNT / A FLEATED CONC BUTT INNER LEAF, CALCON SAE / TRAMCTO BUTT  
 OR SA FOR 12.5mm CAPSOM BATED WALLSAD FOR DOT/DAB ADHESIVE BONDING TO INNER FACE FOR 4m SKM AND 203  
 EMULSION DECOR AND/OR SPECIALTY CAPPED CERAMIC WALL THICK TO UTILITY / INSULATE AREA AS SPECIFIED ON SITE.  
 BETWEEN OUTER BRICK AND INNER BUTT FOR A 150mm CAVITY WITH STAINLESS STEEL CAVITY WALL TIES @ 750mm  
 H12, 450mm BUTT BORED 50mm INTO EXTERIOR TO SLOPE BUTTERS WITH EXTRA TIES TO DOOR/WINDOW REINFORCE 25% AND CURB  
 CAVITIES TO DOOR/WINDOW REINFORCE TO PROVIDE Airtight - AIR TESTS WITH CAVALLK / THERMATE TYPE OR SA INSULATED DOOR  
 INSULATE 150mm CAVITY WITH "CEBUN - BETWEEN" TYPE OR SA FULL - FILL CAVITY WITH INSULATION FROM DOOR TO BARS  
 TO ACQUIRE A MAX 0.18 U/VALUE AS DOCTUNE 22  
 PROVIDE A PROPERLY STANDED STEEL "RECORDIE" THE "STANDARD WALL CONNECTOR TYPE SYSTEM SECURED TO EX,  
 MASONRY AND CAPPED TO SUT CURSING OF NEW MASONRY TO PROVIDE A SECURE / REINFORCE / POSITIVE  
 CONNECTION & NEW LINE MASONRY TO EX, ... IN USE OF ATTENDING TO BOTH AND BOND ... ETC...

SECTIONS OF A "GAS-SAFE" ~~BE~~  
HEATING EQUIPMENT DESIGN.  
ANY INSTALL A SUBMITTER SIZED  
GAS CONTROL/CHANGING, CONTROL  
HEATING, BURNER MANAGED ON THE  
SYSTEM WANTS OF UTILITY YOU  
MAIN'S GAS, WATER, ELECTRIC  
SUPPLIES EXTENDED ACCORDING  
TO BUT WITH A MAN ASSISTED  
HORIZONTAL FIVE AS DUCT  
DIAGRAM 14.  
UPON COMPLETION CERTIFICATION  
FOR INSTALLATION TO BE PROVIDED  
TO APPLICANT FOR GASC  
DELISTED FOR ... RE GAS-SAFE

0.65 N