

next working day
delivery



WhatsApp 07892 71336

The JST SK series is a range of 3phs 415v submersible sewage cutter pumps.

These pumps feature a single channel tungsten carbide tipped impeller running against a grinding diffuser plate causing the shredding action cutting soft solids into smaller parts to pump through the body to waste.

The JST-SK sewage chopper pumps include double oil bathed mechanical seals in a lubricated chamber which offers reliability and longevity to the end user and some degree of protection against accidental dry running.

The JST-SK pump body, volute stand, impeller, lower motor bearing/seal housing and motor top cover are manufactured from cast iron, while the shaft and motor case are from stainless steel.

MODEL	VOLT	OUTLET	LM/HM	Kw	AMP	H x W x L mm	Kg	CODE
JST-08SK	400v	2"	370/15	0.75	1.8	465 x 195 x 315	28	012-780 *
JST-15SK	400v	3"	955/17.5	1.5	3.2	515 x 240 x 375	37	012-782
JST-22SK	400v	3"	1250/20	2.2	4.6	565 x 240 x 405	50	012-784
JST-37SK	400v	4"	1440/25	3.7	7.9	610 x 250 x 405	55	012-786
JST-55SK4	400v	4"	2730/22	5.5	11.5	730 x 420 x 740	140	012-790
JST-75SK4	400v	4"	2935/24	7.5	15.2	750 x 420 x 740	150	012-796
JST-110SK4	400v	6"	3685/27.5	11	22.7	910 x 480 x 900	230	012-805

Supplied complete with 10 metres of power cable and hose tails are supplied with the 2 inch and 3 inch versions.



Shop Now. Pay Later.

Please shop responsibly. 18+ T&Cs apply. Find out more.

Features

- Maximum Head: up to 25m
- Maximum Flow: up to 2200 litres/min
- 415V 3-Phase



Not sure paying online?
Call us to make payment.
Our friendly & helpful team
will be more than happy to assist.

**0333
050 3748**
Calls charged at local rate

Model	Power (kW)	Outlet size	Max Flow Litres/min	Max Head Metres	Weight (kg)
JST 8 SK	0.8	2	370	15	28
JST 15 SK	1.5	3	955	17.5	38