



- GENERAL NOTES
- G1. DO NOT SCALE THIS DRAWING.
- G2. ANY DIMENSIONAL DISCREPANCIES SHOULD BE NOTIFIED TO THE ENGINEER IMMEDIATELY.
- G3. ALL DIMENSIONS ARE IN MILLIMETRES - (mm)
ALL LEVELS ARE IN METRES - (m) AND ARE ABOVE ORDNANCE DATUM AT NEWLYN, CORNWALL UNLESS NOTED OTHERWISE.
- G4. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT, SPECIFICATIONS, DRAWINGS, DETAILS AND OTHER DESIGN INFORMATION.
- G5. ALL DRAWINGS AND WRITTEN MATERIAL CONTAINED WITHIN, CONSTITUTE ORIGINAL AND UNPUBLISHED WORK OF THE ENGINEER AND MAY NOT BE DUPLICATED, USED, REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OR EXPRESS PERMISSION FROM THE ENGINEER.
- G6. ALL INFORMATION CONTAINED IN THIS DOCUMENT IS COPYRIGHT ©
- G7. WHERE THE CONTRACTOR UNDERTAKES OR ENGAGES A THIRD PARTY TO UNDERTAKE TEMPORARY WORKS DESIGN, OR VARIES THE PELL FRISCHMANN DESIGN IN ANY WAY, THEN THE CONTRACTOR WILL TAKE FULL RESPONSIBILITY AND LIABILITY FOR ALL DESIGN ASPECTS, INCLUDING A DESIGN RISK ASSESSMENT. THE CONTRACTOR SHALL INFORM PELL FRISCHMANN OF ANY PROPOSED VARIANCES TO THE DESIGN.

- KEY:
- HB2 KERB - 125mm UPSTAND
PROVIDE AND LAY 125x255mm HB2 PCC KERB WITH 125mm UPSTAND LAID AS DETAILED ON DRAWING 110081-PEL-HGN-01-DE-D-0001.
- BN KERB - 6mm UPSTAND
PROVIDE AND LAY 125x150mm BULLNOSED KERB WITH 6mm UPSTAND LAID AS DETAILED ON DRAWING 110081-PEL-HGN-01-DE-D-0001.
- BN KERB - 25mm UPSTAND
PROVIDE AND LAY 125x150mm BULLNOSED KERB WITH 25mm UPSTAND LAID AS DETAILED ON DRAWING 110081-PEL-HGN-01-DE-D-0001.
- TRANSITION KERB - VARYING UPSTAND
PROVIDE AND LAY TRANSITION KERB AS DETAILED ON DRAWING 110081-PEL-HGN-01-DE-D-0001.
- PROPOSED FULL DEPTH FOOTWAY
SURFACE COURSE: 20mm THICK AC6 DENSE SURF 100/150 (CLAUSE 909).
BINDER COURSE: 60mm THICK AC20 DENSE BIN 100/150 (CLAUSE 906).
SUB-BASE: 150mm THICK TYPE 1 SUB-BASE S.H.W CL. 801, 803.
- VEHICLE OVERRUN - FULL DEPTH
SURFACE COURSE: 20mm THICK AC6 DENSE SURF 100/150 (CLAUSE 909).
BINDER COURSE: 100mm THICK AC20 DENSE BIN 100/150 (CLAUSE 906).
SUB-BASE: 230mm THICK TYPE 1 SUB-BASE S.H.W CL. 801, 803.
- FOOTWAY RESURFACING -
SURFACE COURSE: 20mm THICK AC6 DENSE SURF 100/150 (CLASUE 909)
REGULATING BINDER COURSE: 80mm AC20 DENSE BIN 100/150 (CLAUSE 906)
- PROPOSED UNCONTROLLED TACTILES
400x400mm BUFF COLOUR 'BLISTER' PATTERN TACTILE PAVING

P04	UPDATED TO CLIENT COMMENTS	EP	AH	AH	23.04.26
P03	COMMENTS INCORPORATED	IC	AH	AH	30.03.26
P02	UPDATED TO CORRECT LAYOUT	EP	AH	AH	09.03.26
P01	FIRST ISSUE	IC	EP	AH	11.02.26
REV	DESCRIPTION	DRN	CHK	APP	DATE

Pell Frischmann
4th FLOOR, ONE ST JAMES SQUARE, MANCHESTER, M2 6DN
Telephone +44 (0)161 826 9400
Email: pfmanchester@pellfrischmann.com
www.pellfrischmann.com



**DUMERS LANE
DETAILED DESIGN**

**HIGHWAYS
KERBS AND FOOTWAYS**

Drawing Status			
PRELIMINARY			
Drawn	Name	Date	Status Code
Designed	I.CALGOTRA	11.02.26	S4
Eng Chk	E.PHYTHIAN	11.02.26	Scale
Approved	A.HALL	11.02.26	1:200
Revision			P04

Drawing No. 110081 - PEF - S228-HKF- DR - C - 00001

