

Air Quality Assessment
Hollins Brook Way, Unsworth

Client: JD Sports Fashion PLC

Reference: 9943r1

Date: 30th October 2025



Report Issue

Report Title: Air Quality Assessment - Hollins Brook Way, Unsworth

Report Reference: 9943

Field	Report Version			
	1	2	3	4
Prepared by	Emily Moore			
Position	Graduate Air Quality Consultant			
Reviewed by	Lauren Massingham			
Position	Associate Air Quality Consultant			
Authorised by	Claire Meddings			
Position	Director			
Date of Issue	30 th October 2025			
Comments	-			

Serendipity Labs, Building 7, Exchange Quay, Salford, M5 3EP

info@red-env.co.uk | 0161 706 0075 | www.red-env.co.uk

This report has been prepared by Redmore Environmental Ltd in accordance with the agreed terms and conditions of appointment. Redmore Environmental Ltd cannot accept any responsibility for any use of or reliance on the contents of this report by any third party.

Executive Summary

Redmore Environmental Ltd was commissioned by JD Sports Fashion PLC to undertake an Air Quality Assessment in support of a mixed-use development at Hollins Brook Way, Unsworth, Bury.

An Air Quality Assessment was undertaken to:

- Assess potential impacts associated with fugitive dust emissions during the construction phase of the proposed development;
- Assess potential impacts associated with road transport emissions during the operational phase of the proposed development; and,
- Identify any requirement for relevant mitigation measures.

Potential construction phase impacts from fugitive dust emissions were assessed as a result of earthworks, construction and trackout activities. It is considered that the use of the identified site-specific control measures would provide suitable mitigation for a development of this size and nature and reduce potential impacts to an acceptable level.

Potential impacts during the operational phase of the proposals may occur due to road traffic exhaust emissions associated with vehicles travelling to and from the site. These were assessed using standard screening criteria. Due to the nature of the development, road traffic exhaust emission impacts were not predicted to be significant.

Based on the assessment results, air quality factors are not considered a constraint to planning consent for the proposals.

Table of Contents

1.0	INTRODUCTION	1
1.1	Instruction	1
1.2	Site Location and Context	1
1.3	Assessment Scope	1
2.0	LEGISLATION AND POLICY	2
2.1	Legislation	2
2.2	Local Air Quality Management	4
2.3	Dust	4
2.4	National Planning Policy	5
2.5	National Planning Practice Guidance	6
2.6	Regional Planning Policy	7
2.7	Local Planning Policy	9
2.8	Clean Air Plan	11
3.0	METHODOLOGY	12
3.1	Introduction	12
3.2	Construction Phase Assessment	12
	Step 1 - Screen the Need for an Assessment	12
	Step 2 - Assess the Risk of Dust Impacts	13
	Step 3 - Site-specific Mitigation	18
	Step 4 - Determine Significant Effects	18
3.3	Operational Phase Assessment	18
4.0	BASELINE	20
4.1	Introduction	20
4.2	Local Air Quality Management	20
4.3	Air Quality Monitoring	20
4.4	Background Pollutant Concentrations	21
4.5	Sensitive Receptors	22
5.0	CONSTRUCTION PHASE ASSESSMENT	24
5.1	Introduction	24
5.2	Step 1 - Screen the Need for an Assessment	24
5.3	Step 2a - Define the Potential Dust Emission Magnitude	24
	Earthworks	24
	Construction	24
	Trackout	25

5.4	Step 2b - Define the Sensitivity of the Area	25
	Dust Soiling	25
	Human Health	25
	Ecological	26
5.5	Step 2c - Define the Risk of Dust Impacts	26
5.6	Step 3 - Site-specific Mitigation	27
5.7	Step 4 - Determine Significant Effects	29
6.0	OPERATIONAL PHASE ASSESSMENT	30
6.1	Introduction	30
6.2	Road Vehicle Exhaust Emissions	30
6.3	Interim Planning Guidance for PM _{2.5}	30
7.0	CONCLUSION	32
8.0	ABBREVIATIONS	33

Appendix

Appendix 1 - Curricula Vitae

1.0 INTRODUCTION

1.1 Instruction

Redmore Environmental Ltd was commissioned by JD Sports Fashion PLC to undertake an Air Quality Assessment in support of a mixed-use development at Hollins Brook Way, Unsworth, Bury.

1.2 Site Location and Context

- 1.2.1 The site is located at, Hollins Brook Way, Unsworth, Bury, at approximate National Grid Reference (NGR): 381530, 408675. The relevant Local Authority (LA) is Bury Council (BC). Reference should be made to Figure 1 for a map of the site and surrounding area.
- 1.2.2 The proposed development is for circa 15,000sqft of floor space which will provide ancillary provision i.e. gym and kitchen and associated infrastructure for the consented JD Office Campus.

1.3 Assessment Scope

- 1.3.1 The proposals have the potential to cause air quality impacts at sensitive locations. As such, an Air Quality Assessment was undertaken to:
- Assess potential impacts associated with fugitive dust emissions during the construction phase of the development;
 - Assess potential impacts associated with road transport emissions during the operational phase of the development; and,
 - Identify any requirement for relevant mitigation measures.
- 1.3.2 This is detailed in the following report.

2.0 LEGISLATION AND POLICY

2.1 Legislation

2.1.1 The Air Quality Standards Regulations (2010) and subsequent amendments include Air Quality Limit Values (AQLVs) for the following pollutants:

- Nitrogen dioxide (NO₂);
- Sulphur dioxide;
- Lead;
- Particulate matter with an aerodynamic diameter of less than 10µm (PM₁₀);
- Particulate matter with an aerodynamic diameter of less than 2.5µm (PM_{2.5});
- Benzene; and,
- Carbon monoxide.

2.1.2 Air Quality Target Values were also provided for several additional pollutants. It should be noted that the AQLV for PM_{2.5} stated in the Air Quality Standards Regulations (2010) was amended in the Environment (Miscellaneous Amendments) (EU Exit) Regulations (2020).

2.1.3 The Air Quality Strategy (AQS) was produced by the Department for Environment, Food and Rural Affairs (DEFRA) and published on 28th April 2023¹. The document contains standards, objectives and measures for improving ambient air quality, including a number of Air Quality Objectives (AQOs). These are maximum ambient pollutant concentrations that are not to be exceeded either without exception or with a permitted number of exceedences over a specified timescale. These are generally in line with the AQLVs, although the requirements for the determination of compliance vary.

2.1.4 The Environmental Improvement Plan 2023² was published in January 2023, providing long term and Interim Targets in order to reduce population exposure to PM_{2.5}. The Concentration Target for 2040 was subsequently adopted in the Environmental Targets (Fine Particulate Matter) (England) Regulations (2023).

¹ AQS: Framework for Local Authority Delivery, DEFRA, 2023.

² Environmental Improvement Plan 2023, DEFRA, 2023.

2.1.5 Table 1 presents the AQOs, Interim Target and Concentration Target for pollutants considered within this assessment.

Table 1 Air Quality Objectives/Interim Target/Concentration Target

Pollutant	Air Quality Objective/Interim Target/Concentration Target	
	Concentration ($\mu\text{g}/\text{m}^3$)	Averaging Period
NO ₂	40	Annual mean
	200	1-hour mean, not to be exceeded on more than 18 occasions per annum
PM ₁₀	40	Annual mean
	50	24-hour mean, not to be exceeded on more than 35 occasions per annum
PM _{2.5}	12 ^(a)	Annual mean
	10 ^(b)	Annual mean

Note: (a) Interim Target to be achieved by end of January 2028.

(b) Concentration Target to be achieved by 2040.

2.1.6 Table 2 summarises the advice provided in DEFRA guidance³ on where the AQOs for pollutants considered within this report apply.

Table 2 Examples of Where the Air Quality Objectives Apply

Averaging Period	Objective Should Apply At	Objective Should Not Apply At
Annual mean	All locations where members of the public might be regularly exposed Building façades of residential properties, schools, hospitals, care homes etc.	Building façades of offices or other places of work where members of the public do not have regular access Hotels, unless people live there as their permanent residence Gardens of residential properties Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term

³ Local Air Quality Management Technical Guidance (TG22), DEFRA, 2022.

Averaging Period	Objective Should Apply At	Objective Should Not Apply At
24-hour mean	All locations where the annual mean objective would apply, together with hotels Gardens of residential properties	Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term
1-hour mean	All locations where the annual mean and 24 and 8-hour mean objectives apply. Kerbside sites (for example, pavements of busy shopping streets) Those parts of car parks, bus stations and railway stations etc which are not fully enclosed, where members of the public might reasonably be expected to spend one hour or more Any outdoor locations where members of the public might reasonably be expected to spend one hour or longer	Kerbside sites where the public would not be expected to have regular access

2.2 Local Air Quality Management

- 2.2.1 LAs are required to periodically review and assess air quality within their area of jurisdiction under the system of Local Air Quality Management (LAQM). This review and assessment of air quality involves comparing present and likely future pollutant concentrations against the AQOs. If it is predicted that levels at locations of relevant exposure, as summarised in Table 2, are likely to be exceeded, the LA is required to declare an Air Quality Management Area (AQMA). For each AQMA the LA is required to produce an Air Quality Action Plan, the objective of which is to reduce pollutant concentrations in pursuit of the AQOs.

2.3 Dust

- 2.3.1 The main requirements with respect to dust control from industrial or trade premises not regulated under the Environmental Permitting (England and Wales) Regulations (2016) and subsequent amendments, such as construction sites, is that provided in Section 79 of Part III of the Environmental Protection Act (1990). The Act defines nuisance as:

"any dust, steam, smell or other effluvia arising on industrial, trade or business premises and being prejudicial to health or a nuisance."

2.3.2 Enforcement of the Act, in regard to nuisance, is currently under the jurisdiction of the local Environmental Health Department, whose officers are deemed to provide an independent evaluation of nuisance. If the LA is satisfied that a statutory nuisance exists, or is likely to occur or happen again, it must serve an Abatement Notice under Part III of the Environmental Protection Act (1990). The only defence is to show that the process to which the nuisance has been attributed and its operation are being controlled according to best practicable means.

2.4 National Planning Policy

2.4.1 The revised National Planning Policy Framework⁴ (NPPF) was published in December 2024 and amended in February 2025. The document sets out the Government's planning policies for England and how these are expected to be applied.

2.4.2 The purpose of the planning system is to contribute to the achievements of sustainable development. In order to ensure this, the NPPF recognises three overarching objectives including the following of relevance to air quality:

"c) an environmental objective - to protect and enhance our natural, built and historic environment; including making effective use of land, improving biodiversity, using natural resources prudently, minimising waste and pollution, and mitigating and adapting to climate change, including moving to a low carbon economy."

2.4.3 Chapter 15 of the NPPF details objectives in relation to conserving and enhancing the natural environment. It states that:

"Planning policies and decisions should contribute to and enhance the natural and local environment by:

[...]

e) preventing new and existing development from contributing to, or being put at unacceptable risk from, or being adversely affected by, unacceptable levels of

⁴ NPPF, Ministry of Housing, Communities and Local Government, 2024.

soil, air, water or noise pollution or land instability. Development should, wherever possible, help to improve local environmental conditions such as air and water quality [...]"

- 2.4.4 The NPPF specifically recognises air quality as part of delivering sustainable development and states that:

"Planning policies and decisions should sustain and contribute towards compliance with relevant limit values or national objectives for pollutants, taking into account the presence of Air Quality Management Areas and Clean Air Zones, and the cumulative impacts from individual sites in local areas. Opportunities to improve air quality or mitigate impacts should be identified, such as through traffic and travel management, and green infrastructure provision and enhancement. So far as possible these opportunities should be considered at the plan-making stage, to ensure a strategic approach and limit the need for issues to be reconsidered when determining individual applications. Planning decisions should ensure that any new development in Air Quality Management Areas and Clean Air Zones is consistent with the local air quality action plan."

- 2.4.5 The implications of the NPPF have been considered throughout this assessment.

2.5 **National Planning Practice Guidance**

- 2.5.1 The National Planning Practice Guidance⁵ (NPPG) web-based resource was launched by the Department for Communities and Local Government to support the NPPF and make it more accessible. The air quality pages are summarised under the following headings:

1. What air quality considerations does planning need to address?
2. What is the role of plan-making with regard to air quality?
3. Are air quality concerns relevant to neighbourhood planning?
4. What information is available about air quality?
5. When could air quality be relevant to the planning development management process?
6. What specific issues may need to be considered when assessing air quality impacts?

⁵ <https://www.gov.uk/guidance/air-quality--3>.

7. How detailed does an air quality assessment need to be?
8. How can an impact on air quality be mitigated?

2.5.2 These were reviewed and the relevant guidance considered as necessary throughout the undertaking of this assessment.

2.6 Regional Planning Policy

2.6.1 The Places for Everyone Plan (PfEP)⁶ was produced by the nine Greater Manchester Combined Authorities (GMCAs) of Bolton, Bury, Manchester, Oldham, Rochdale, Salford, Tameside, Trafford and Wigan, and became part of the statutory development plan for each of the Councils on 21st March 2024.

2.6.2 A review of the PfEP indicated the following policies of relevance to air quality that have been considered throughout this assessment:

"Policy JP:S5: Clean Air

A comprehensive range of measures will be taken to support improvements in air quality, focusing particularly on locations where people live, where children learn and play, where there are impacts on the green infrastructure network and where air quality targets are not being met, including:

1. Locating and designing development, and focusing transport investment, so as to reduce reliance on forms of transport that generate air pollution;
2. Determining planning applications having regard to the most recent development and planning control guidance published jointly by the Institute of Air Quality Management (IAQM) and Environmental Protection UK (EPUK), and the most recent IAQM Guidance on the Assessment of Dust from Demolition and Construction, or relevant successor guidance, including the requirement for developers to submit construction management plans as appropriate;

⁶ PfEP, GMCA, 2024.

3. Requiring applications for developments that could have an adverse impact on air quality to submit relevant air pollution data so that adverse impacts on air quality can be fully assessed and development only permitted where they are acceptable and/or suitable mitigation can be provided;
4. Restricting developments that would generate significant point source pollution such as some types of industrial activity and energy generation;
5. Significantly expanding the existing commercial network of electric vehicle charging points, both for public and private use, including as part of new developments;
6. Implementing the Clean Air Plan and associated measures;
7. Facilitating the more sustainable distribution of goods within the urban area, including through accommodating urban consolidation centres and urban distribution centres that use ultra-low-emission vehicles, and local delivery facilities to reduce repeat delivery attempts;
8. Designing streets to avoid trapping air pollution at ground level, including through the appropriate location and scale of buildings and trees;
9. Controlling traffic and parking within and around schools, early years sites and other locations that are particularly sensitive to air quality;
10. Promoting actions that help remove pollutants from the air, such as enhancing the green infrastructure network and using innovative building materials that capture air pollutants; and,
11. Development should be located in areas that maximise the use of sustainable travel modes and be designed to minimise exposure to high levels of air pollution, particularly for vulnerable users."

"Policy JP-P1 Sustainable Places

We aim to become one of the most liveable city regions in the world, consisting of

a series of beautiful, healthy and varied places, each having the following key attributes that all development, wherever appropriate, should be consistent with:

[...]

15. Comfortable and inviting, with indoor and outdoor environments:

A. Offering a high level of amenity that minimises exposure to pollution; and,

[...]."

2.6.3 The above policies were taken into consideration throughout the undertaking of the assessment.

2.7 Local Planning Policy

2.7.1 The Bury Unitary Development Plan (UDP)⁷ was adopted by BC on 29th August 1997. A review of the document indicated that the policies of relevance to the assessment have been replaced by JP-P1 and JP-S5 in the PfEP⁸ as outlined above.

2.7.2 The Draft Bury Local Plan⁹ is currently undergoing consultation and will form part of the overall BC Development Plan once formally adopted. Review of the document indicated the following policies of relevance to this assessment:

"Policy LP-CM2: New development and health

The Council will ensure that new development makes a positive contribution towards the health and wellbeing of the Borough's communities by:

[...]

e. Helping to improve air quality and other pollution that may impact on human health;

⁷ Bury UDP, BC, 1997.

⁸ PfEP, GMCA, 2024.

⁹ Draft Bury Local Plan, BC, 2025.

[...]"

"Policy LP-API: Air quality and pollution control

The Council will prevent both new and existing development from contributing to, or being adversely affected by, unacceptable levels of pollution and poor air quality.

In assessing the potential impact of pollution, the Council will have regard to:

- a) Potential impacts on human health and amenity;
- b) The proximity and sensitivity of uses that could be affected by the pollution;
- c) Existing levels of pollution, including Air Quality Management Areas within the Borough;
- d) The sensitivity of natural resources and heritage assets that may be affected; and
- e) Any relevant strategies and targets for pollution control and reduction.

Where new development gives rise to the potential for unacceptable adverse impacts from pollution, the Council will require applicants to submit an assessment of the pollution impacts which includes proposed measures to avoid, minimise or mitigate pollution impacts.

Where necessary, the Council will impose planning conditions and/or obligations to ensure that the impacts of pollution are being effectively monitored and that the proposed measures to avoid, minimise or mitigate pollution impacts are being effectively implemented.

The Council will not permit development where an applicant is unable to satisfactorily demonstrate that measures are capable of being put in place to avoid, minimise or mitigate pollution impacts."

2.7.3 The above policies were taken into consideration throughout the undertaking of the assessment.

2.8 Clean Air Plan

2.8.1 The UK Government has instructed a number of LAs to take rapid action to reduce harmful roadside levels of NO₂ within their areas of jurisdiction in the quickest possible timeframe. The GMCA and Transport for Greater Manchester (TfGM) have collaborated to develop a Clean Air Plan (CAP) to ensure Greater Manchester achieves compliance with the relevant AQOs for NO₂ by 2026 at the latest. The initial CAP proposal included implementation of a Class C charging Clean Air Zone. The GMCA subsequently updated the CAP proposals¹⁰ to comprise an investment-led, non-charging approach. This was approved by the UK Government on 23rd January 2025. The implications of the CAP were taken into account during the undertaking of this assessment.

¹⁰ Case for a New GM Clean Air Plan, GMCA and TfGM, 2022.

3.0 METHODOLOGY

3.1 Introduction

3.1.1 The proposed development has the potential to cause air quality impacts during the construction and operational phases. These have been assessed in accordance with the following methodology.

3.2 Construction Phase Assessment

3.2.1 There is the potential for fugitive dust emissions to occur as a result of construction phase activities. These have been assessed in accordance with the methodology outlined within the Institute of Air Quality Management (IAQM) document 'Guidance on the Assessment of Dust from Demolition and Construction V2.2'¹¹.

3.2.2 Activities on the proposed construction site have been divided into three types to reflect their different potential impacts. These are:

- Earthworks;
- Construction; and,
- Trackout.

3.2.3 The potential for dust emissions was assessed for each activity that is likely to take place and considered three separate dust effects:

- Annoyance due to dust soiling;
- Harm to ecological receptors; and,
- The risk of health effects due to a significant increase in exposure to PM₁₀.

3.2.4 The assessment steps are detailed below.

Step 1 - Screen the Need for an Assessment

3.2.5 Step 1 screens the requirement for a more detailed assessment. Should human receptors

¹¹ Guidance on the Assessment of Dust from Demolition and Construction V2.2, IAQM, 2024.

be identified within 250m from the boundary or 50m from the construction vehicle route up to 250m from the site entrance, then the assessment proceeds to Step 2. Additionally, should ecological receptors be identified within 50m of the site or the construction vehicle route up to 250m from the site entrance, then the assessment also proceeds to Step 2.

- 3.2.6 Should sensitive receptors not be present within the relevant distances then **negligible** impacts would be expected and further assessment is not necessary.

Step 2 - Assess the Risk of Dust Impacts

- 3.2.7 Step 2 assesses the risk of potential dust impacts. A site is allocated a risk category based on two factors:

- The scale and nature of the works, which determines the magnitude of dust arising as: small, medium or large (Step 2A); and,
- The sensitivity of the area to dust impacts, which can be defined as low, medium or high sensitivity (Step 2B).

- 3.2.8 The two factors are combined in Step 2C to determine the risk of dust impacts without mitigation applied.

- 3.2.9 Step 2A defines the potential magnitude of dust emission through the construction phase. The relevant criteria are summarised in Table 3.

Table 3 Construction Dust - Magnitude of Emission

Magnitude	Activity	Criteria
Large	Earthworks	• Total site area greater than 110,000m² • Potentially dusty soil type (e.g. clay, which will be prone to suspension when dry due to small particle size) • More than 10 heavy earth moving vehicles active at any one time • Formation of bunds greater than 6m in height
	Construction	• Total building volume greater than 75,000m³ • On site concrete batching • Sandblasting

Magnitude	Activity	Criteria
	Trackout	• More than 50 Heavy Duty Vehicle (HDV) trips per day • Potentially dusty surface material (e.g. high clay content) • Unpaved road length greater than 100m
Medium	Earthworks	• Total site area 18,000m² to 110,000m² • Moderately dusty soil type (e.g. silt) • 5 to 10 heavy earth moving vehicles active at any one time • Formation of bunds 3m to 6m in height
	Construction	• Total building volume 12,000m³ to 75,000m³ • Potentially dusty construction material (e.g. concrete) • On site concrete batching
	Trackout	• 20 to 50 HDV trips per day • Moderately dusty surface material (e.g. high clay content) • Unpaved road length 50m to 100m
Small	Earthworks	• Total site area less than 18,000m² • Soil type with large grain size (e.g. sand) • Less than 5 heavy earth moving vehicles active at any one time • Formation of bunds less than 3m in height
	Construction	• Total building volume less than 12,000m³ • Construction material with low potential for dust release (e.g. metal cladding or timber)
	Trackout	• Less than 20 HDV trips per day • Surface material with low potential for dust release • Unpaved road length less than 50m

3.2.10 Step 2B defined the sensitivity of the area around the development to potential dust impacts. The sensitivities of specific receptors are summarised in Table 4.

Table 4 Construction Dust - Sensitivities of People and Ecological Receptors

Receptor Sensitivity	Examples	
	Human Receptors	Ecological Receptors
High	- Users expect high levels of amenity - High aesthetic or value property - People expected to be present continuously for extended periods of time - Locations where members of the public are exposed over a time period relevant to the AQO for PM₁₀. e.g. residential properties, hospitals, schools and residential care homes	Internationally or nationally designated site e.g. Special Area of Conservation
Medium	- Users would expect to enjoy a reasonable level of amenity - Aesthetics or value of their property could be diminished by soiling - People or property wouldn't reasonably be expected to be present here continuously or regularly for extended periods as part of the normal pattern of use of the land e.g. parks and places of work	Nationally designated site e.g. Sites of Special Scientific Interest
Low	- Enjoyment of amenity would not reasonably be expected - Property would not be expected to be diminished in appearance - Transient exposure, where people would only be expected to be present for limited periods. e.g. public footpaths, playing fields, shopping streets, farmland, short term car parks and roads	Locally designated site e.g. Local Nature Reserve

3.2.11 The criteria for determining the sensitivity of the area to dust soiling effects on people and property is summarised in Table 5.

Table 5 Construction Dust - Sensitivity of the Area to Dust Soiling Effects on People and Property

Receptor Sensitivity	Number of Receptors	Distance from the Source (m)			
		Less than 20	Less than 50	Less than 100	Less than 250
High	More than 100	High	High	Medium	Low
	10 - 100	High	Medium	Low	Low

Receptor Sensitivity	Number of Receptors	Distance from the Source (m)			
		Less than 20	Less than 50	Less than 100	Less than 250
	1 - 10	Medium	Low	Low	Low
Medium	More than 1	Medium	Low	Low	Low
Low	More than 1	Low	Low	Low	Low

3.2.12 Table 6 outlines the criteria for determining the sensitivity of the area to human health impacts.

Table 6 Construction Dust - Sensitivity of the Area to Human Health Impacts

Receptor Sensitivity	Background Annual Mean PM ₁₀ Concentration	Number of Receptors	Distance from the Source (m)			
			Less than 20	Less than 50	Less than 100	Less than 250
High	Greater than 32µg/m ³	More than 100	High	High	High	Medium
		10 - 100	High	High	Medium	Low
		1 - 10	High	Medium	Low	Low
	28 - 32µg/m ³	More than 100	High	High	Medium	Low
		10 - 100	High	Medium	Low	Low
		1 - 10	High	Medium	Low	Low
	24 - 28µg/m ³	More than 100	High	Medium	Low	Low
		10 - 100	High	Medium	Low	Low
		1 - 10	Medium	Low	Low	Low
	Less than 24µg/m ³	More than 100	Medium	Low	Low	Low
		10 - 100	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low
Medium	Greater than 32µg/m ³	More than 10	High	Medium	Low	Low
		1 - 10	Medium	Low	Low	Low
	28 - 32µg/m ³	More than 10	Medium	Low	Low	Low
		1 - 10	Low	Low	Low	Low

Receptor Sensitivity	Background Annual Mean PM ₁₀ Concentration	Number of Receptors	Distance from the Source (m)			
			Less than 20	Less than 50	Less than 100	Less than 250
	24 - 28µg/m ³	More than 10	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low
	Less than 24µg/m ³	More than 10	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low
Low	-	1 or more	Low	Low	Low	Low

3.2.13 Table 7 outlines the criteria for determining the sensitivity of the area to ecological impacts.

Table 7 Construction Dust - Sensitivity of the Area to Ecological Impacts

Receptor Sensitivity	Distance from the Source (m)	
	Less than 20	Less than 50
High	High	Medium
Medium	Medium	Low
Low	Low	Low

3.2.14 Step 2C combines the dust emission magnitude with the sensitivity of the area to determine the risk of unmitigated impacts.

3.2.15 Table 8 outlines the risk category from earthworks, construction and trackout activities.

Table 8 Construction Dust - Dust Risk Category from Earthworks, Construction and Trackout Activities

Receptor Sensitivity	Dust Emission Magnitude		
	Large	Medium	Small
High	High	Medium	Low
Medium	Medium	Medium	Low
Low	Low	Low	Negligible

Step 3 - Site-specific Mitigation

3.2.16 Step 3 requires the identification of site-specific mitigation measures within the IAQM guidance¹² to reduce potential dust impacts based upon the relevant risk categories identified in Step 2. For sites with **negligible** risk, mitigation measures beyond those required by legislation are not required. However, additional controls may be applied as part of good practice.

Step 4 - Determine Significant Effects

3.2.17 Once the risk of dust impacts has been determined and the appropriate mitigation measures identified, the final step is to determine the significance of any residual impacts. For almost all construction activity, the aim should be to control effects through the use of effective mitigation. Experience shows that this is normally possible. Hence the residual effect will normally be **not significant**.

3.2.18 The determination of significance relies on professional judgement and reasoning should be provided as far as practicable. The IAQM guidance suggests the provision of details of the assessor's qualifications and experience. These are provided in Appendix 1.

3.3 Operational Phase Assessment

3.3.1 The development has the potential to increase concentrations of NO₂, PM₁₀ and PM_{2.5} as a result of road traffic exhaust emissions associated with vehicles travelling to and from the site during the operational phase. An assessment was therefore undertaken using the criteria contained within the IAQM 'Land-Use Planning & Development Control: Planning for Air Quality'¹³ guidance to determine the potential for trips generated by the development to affect local air quality.

3.3.2 The following criteria are provided to help establish when an assessment of potential impacts on the local area is likely to be considered necessary:

- The development leads to a change of Light Duty Vehicle (LDV) flows of:

¹² Guidance on the Assessment of Dust from Demolition and Construction V2.2, IAQM, 2024.

¹³ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

- More than 100 Annual Average Daily Traffic (AADT) within an AQMA;
- More than 500 AADT outside of an AQMA;
- The development leads to a change of HDV flows of:
 - More than 25 AADT within an AQMA;
 - More than 100 AADT outside of an AQMA;
- Introduce a new junction that would cause traffic flow to change behaviour with respect to acceleration/deceleration or introduce queueing traffic where there previously wasn't any (such as a roundabout or traffic lights); and,
- Introduce one or more significant combustion processes where there is a risk of impact to relevant receptors.

3.3.3 Should these criteria not be met, then the IAQM guidance¹⁴ considers air quality impacts associated with a scheme to be **not significant** and no further assessment is required.

¹⁴ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

4.0 BASELINE

4.1 Introduction

- 4.1.1 Existing air quality conditions in the vicinity of the proposed development site were identified in order to provide a baseline for assessment. These are detailed in the following Sections.

4.2 Local Air Quality Management

- 4.2.1 As required by the Environment Act (1995), as amended by the Environment Act (2021), BC has undertaken Review and Assessment of air quality within its area of jurisdiction. This process has indicated that annual mean concentrations of NO₂ are above the AQO within the borough. As such, a number of roads within Bury have been included within the GMCA AQMA. This is described as follows:

"This is the part of the Greater Manchester Combined Authority AQMA located within the Bury Council area."

- 4.2.2 The AQMA is located approximately 500m east and 900m west of the development. As such, there is the potential for vehicles travelling to and from the site to increase pollution levels in this sensitive area. This has been considered throughout the assessment.
- 4.2.3 BC has concluded that concentrations of all other pollutants considered within the AQMA are currently below the relevant AQOs. As such, no further AQMAs have been designated.

4.3 Air Quality Monitoring

- 4.3.1 Monitoring of pollutant levels is undertaken by BC throughout its area of jurisdiction. Recent NO₂ concentrations recorded in the vicinity of the development, as provided in GMCA's '2024 Air Quality Annual Status Report (ASR)'¹⁵ and 'CAP NO₂ Diffusion Tube Results 2011-2024'¹⁶, are shown in Table 9.

¹⁵ 2024 Air Quality ASR, GMCA, 2025.

¹⁶ Greater Manchester LAQM and CAP NO₂ Diffusion Tube Results 2011-2024, GMCA, 2024.

Table 9 Monitoring Results

Monitoring Site		Monitored Annual Mean NO ₂ Concentration (µg/m ³)		
		2022	2023	2024
BU3ANO, BU3BNO, BU3CNO	BU3 Bury Roadside Whitefield (AURN)	20.9	18.8	16.7
CAP_BURY _041 ^(a)	Whitefield	26.3	-	-

Note: (a) Monitor commissioned and decommissioned in 2022.

4.3.2 As shown in Table 9, annual mean NO₂ concentrations were below the AQO of 40µg/m³ at all monitors in recent years. Reference should be made to Figure 2 for a map of the survey positions.

4.3.3 BC does not undertake monitoring of PM₁₀ or PM_{2.5} concentrations within the vicinity of the site.

4.4 Background Pollutant Concentrations

4.4.1 Predictions of background pollutant concentrations on a 1km by 1km grid basis have been produced by DEFRA for the entire of the UK to assist LAs in their Review and Assessment of air quality. The proposed development site is located in grid square NGR: 381500, 408500. Data for this location was downloaded from the DEFRA website¹⁷ for the purpose of the assessment and are summarised in Table 10.

Table 10 Background Pollutant Concentration Predictions

Pollutant	Predicted 2025 Background Pollutant Concentration (µg/m ³)
NO ₂	12.98
PM ₁₀	11.75
PM _{2.5}	6.87

4.4.2 As shown in Table 10, predicted background NO₂, PM₁₀ and PM_{2.5} concentrations are below the relevant AQOs and Concentration Target at the development site.

¹⁷ <http://uk-air.defra.gov.uk/data/laqm-background-maps?year=2021>.

4.5 Sensitive Receptors

- 4.5.1 A sensitive receptor is defined as any location which may be affected by changes in air quality as a result of a development. Receptors sensitive to potential dust impacts during earthworks and construction were identified from a desk-top study of the area up to 250m from the development boundary. These are summarised in Table 11.

Table 11 Earthworks and Construction Dust Sensitive Receptors

Distance from Site Boundary (m)	Approximate Number of Human Receptors	Approximate Number of Ecological Receptors
Up to 20	More than 100	1
Up to 50	More than 100	1
Up to 100	More than 100	-
Up to 250	More than 100	-

- 4.5.2 The ecological receptor identified in Table 11 is Hollins Vale Local Nature Reserve (LNR), which is adjacent to the southern boundary of the site. Reference should be made to Figure 3 for a map of the designation extents.
- 4.5.3 Receptors sensitive to potential dust impacts from trackout were identified from a desk-top study of the area up to 50m from the road network within 250m of the site access. These are summarised in Table 12.

Table 12 Trackout Dust Sensitive Receptors

Distance from Site Access Route (m)	Approximate Number of Human Receptors	Approximate Number of Ecological Receptors
Up to 20	More than 100	0
Up to 50	More than 100	0

- 4.5.4 Based on the criteria shown in Table 4, the sensitivity of the receiving environment to potential dust impacts is considered to be **high** sensitivity. This was because the identified receptors included residential properties.

4.5.5 The ecological receptor identified in Table 11 is an LNR. Based on the criteria shown in Table 4, the sensitivity to potential dust impacts was classified as **low**.

5.0 CONSTRUCTION PHASE ASSESSMENT

5.1 Introduction

- 5.1.1 There is the potential for air quality impacts as a result of the construction of the proposed development. These are assessed in the following Sections.

5.2 Step 1 - Screen the Need for an Assessment

- 5.2.1 The undertaking of activities such as excavation, groundworks, cutting, concrete batching, construction and storage of materials has the potential to result in fugitive dust emissions throughout the construction phase. Vehicle movements both on-site and on the local road network also have the potential to result in the re-suspension of dust from haul roads and highway surfaces.
- 5.2.2 The potential for impacts at sensitive locations depends significantly on local meteorology during the undertaking of dust generating activities, with the most significant effects likely to occur during dry and windy conditions.
- 5.2.3 The desk-study undertaken to inform the baseline identified a number of sensitive receptors within 250m of the site boundary. As such, a detailed assessment of potential dust impacts was required.

5.3 Step 2a - Define the Potential Dust Emission Magnitude

Earthworks

- 5.3.1 Earthworks will primarily involve excavating material, haulage, tipping and stockpiling, as well as site levelling and landscaping. The area of the proposed development site is between 18,000m² and 110,000m². In accordance with the criteria outlined in Table 3, the magnitude of potential dust emissions from earthworks is therefore **medium**.

Construction

- 5.3.2 Due to the nature of the development, the total building volume is likely to be between 12,000m³ and 75,000m³. In accordance with the criteria outlined in Table 3, the magnitude

of potential dust emissions from construction is therefore **medium**.

Trackout

- 5.3.3 Based on the site area, it is anticipated that the unpaved road length will be less than 50m. In accordance with the criteria outlined in Table 3, the magnitude of potential dust emissions from trackout is therefore **small**.

5.4 Step 2b - Define the Sensitivity of the Area

Dust Soiling

- 5.4.1 Table 11 shows that there are more than 100 **high** sensitivity receptors within 20m of the site boundary. The sensitivity of the area with respect to dust soiling from earthworks and construction, as defined using the criteria summarised in Table 5, is therefore considered to be **high**.
- 5.4.2 Table 12 shows that there are more than 100 **high** sensitivity receptors within 20m of the road network within 250m of the site access. The sensitivity of the area with respect to dust soiling from trackout, as defined using the criteria summarised in Table 5, is therefore considered to be **high**.

Human Health

- 5.4.3 Table 10 shows the 2025 annual mean PM₁₀ background concentration at the site is 11.75µg/m³. As shown in Table 6, where the background annual mean PM₁₀ concentration is below 24µg/m³ and there are more than 100 **high** sensitivity receptors within 20m of the site boundary, the sensitivity of the area with respect to human health from earthworks and construction is considered to be **medium**.
- 5.4.4 There are more than 100 **high** sensitivity receptors within 20m of the road network within 250m of the site access. The sensitivity of the area with respect to human health from trackout, as defined using the criteria in Table 6, is therefore considered to be **medium**.

Ecological

5.4.5 Table 11 shows that there is one low sensitivity receptor within 20m of the site boundary. The sensitivity of the area with respect to ecological impacts from earthworks and construction, as defined using the criteria summarised in Table 7 is therefore considered to be **low**.

5.4.6 There are no ecological receptors within 50m of the road network within 250m of the site access. As such, ecological impacts associated with fugitive dust emissions during trackout have not been considered further.

5.5 Step 2c - Define the Risk of Dust Impacts

5.5.1 The derived dust emission magnitude for each activity has been combined with the sensitivity of the area to determine the risk of unmitigated impacts in line with the methodology set out in Table 8. A summary of the risk from each dust generating activity is provided in Table 13.

Table 13 Summary of Potential Unmitigated Dust Risks

Potential Impact	Activity	Step 2A - Dust Emission Magnitude	Step 2B - Sensitivity of the Area	Step 2C - Risk
Dust Soiling	Earthworks	Medium	High	Medium
	Construction	Medium	High	Medium
	Trackout	Small	High	Low
Human Health	Earthworks	Medium	Medium	Medium
	Construction	Medium	Medium	Medium
	Trackout	Small	Medium	Low
Ecological	Earthworks	Medium	Low	Low
	Construction	Medium	Low	Low

5.5.2 As indicated in Table 13, the potential risk of dust soiling is medium from earthworks and construction and **low** from trackout. The potential risk of human health impacts is **medium**

from earthworks and construction and **low** from trackout.. The potential risk of ecological impacts is **low** from earthworks and construction.

5.5.3 It should be noted that the potential for impacts depends significantly on the distance between the dust generating activity and receptor location. Risk was predicted based on a worst-case scenario of works being undertaken at the site boundary closest to each sensitive area. Therefore, actual risk is likely to be lower than that predicted during the majority of the construction phase.

5.6 **Step 3 - Site-specific Mitigation**

5.6.1 The IAQM guidance¹⁸ provides potential mitigation measures to reduce impacts as a result of fugitive dust emissions during the construction phase. These have been adapted for the development site as summarised in Table 14. These may be reviewed prior to the commencement of construction works and incorporated into a Construction Environmental Management Plan or similar if required by the LA.

Table 14 Fugitive Dust Emission Mitigation Measures

Issue	Control Measure
Communications	• Develop and implement a stakeholder communications plan that includes community engagement before work commences on site • Display the name and contact details of person(s) accountable for air quality and dust issues on the site boundary. This may be the environment manager/engineer or the site manager • Display the head or regional office contact information • Develop and implement a Dust Management Plan, which may include measures to control other emissions, approved by the LA
Site management	• Record all dust and air quality complaints, identify cause(s), take appropriate measures to reduce emissions in a timely manner, and record the measures taken • Make the complaints log available to the LA upon request • Record any exceptional incidents that cause dust and/or air emissions, either on- or off- site, and the action taken to resolve the situation in the log book

¹⁸ Guidance on the Assessment of Dust from Demolition and Construction V2.2, IAQM, 2024.

Issue	Control Measure
Monitoring	• Undertake daily on-site and off-site inspection, where receptors (including roads) are nearby, to monitor dust, record inspection results, and make the log available to the LA upon request • Carry out regular site inspections, record inspection results, and make an inspection log available to the LA upon request • Increase the frequency of site inspections when activities with a high potential to produce dust are being carried out and during prolonged dry or windy conditions
Site preparation	• Plan site layout so that machinery and dust causing activities are located away from receptors, as far as is possible • Erect solid screens or barriers around dusty activities or the site boundary that are at least as high as any stockpiles on site • Avoid site runoff of water or mud • Keep site fencing, barriers and scaffolding clean using wet methods • Remove materials that have a potential to produce dust from site as soon as possible, unless being re-used • Cover, seed or fence stockpiles to prevent wind whipping
Operating vehicle/machinery and sustainable travel	• Ensure all vehicles switch off engines when stationary - no idling vehicles • Avoid the use of diesel or petrol powered generators and use mains electricity or battery powered equipment where practicable
Operations	• Only use cutting, grinding or sawing equipment fitted or in conjunction with suitable dust suppression techniques • Ensure an adequate water supply on the site for effective dust suppression, using non-potable water where possible and appropriate • Use enclosed chutes and conveyors and covered skips • Minimise drop heights and use fine water sprays wherever appropriate
Waste management	• Avoid bonfires and burning of waste materials
Construction	• Avoid scabbling (roughening of concrete surfaces) if possible • Ensure sand and other aggregates are stored in bunded areas and are not allowed to dry out • Ensure bulk cement and other fine powder materials are delivered in enclosed tankers and stored in silos with suitable emission control systems to prevent escape of material and overfilling during delivery
Trackout	• Use water-assisted dust sweeper(s) on the access and local roads • Ensure vehicles entering and leaving sites are covered to prevent escape of materials during transport. • Implement a wheel washing system

5.7 **Step 4 - Determine Significant Effects**

- 5.7.1 Assuming the relevant mitigation measures outlined in Table 14 are implemented, the residual impact from all dust generating activities is predicted to be **not significant**, in accordance with the IAQM guidance¹⁹.

¹⁹ Guidance on the Assessment of Dust from Demolition and Construction V2.2, IAQM, 2024.

6.0 OPERATIONAL PHASE ASSESSMENT

6.1 Introduction

- 6.1.1 There is the potential for air quality impacts as a result of the operation of the proposed development. These are assessed in the following Sections.

6.2 Road Vehicle Exhaust Emissions

- 6.2.1 The development has the potential to increase concentrations of NO₂, PM₁₀ and PM_{2.5} as a result of road traffic exhaust emissions associated with vehicles travelling to and from the site during the operational phase. The proposals have therefore been assessed against the IAQM Stage 1²⁰ screening criteria detailed in Section 3.3.
- 6.2.2 Due to the nature of the development comprising circa 15,000sqft of floor space which will provide ancillary provision for the consented JD office Campus, there will not be any new vehicle trips associated with the scheme. All vehicles would already be on the network travelling to the consented offices.
- 6.2.3 As such, potential air quality impacts associated with the operational phase road vehicle exhaust emissions are predicted to be **not significant**, in accordance with the IAQM criteria shown in Section 3.3.

6.3 Interim Planning Guidance for PM_{2.5}

- 6.3.1 Interim Planning Guidance²¹ on the consideration of the PM_{2.5} targets identified in the Environment Act (2021) in planning decisions has been produced by DEFRA. This requires evidence that the key sources of air pollution within a development have been identified and appropriate action to minimise emissions of PM_{2.5} and its precursors as far as is reasonably practicable be provided in support of planning applications. To assist the process, two questions and associated considerations are provided. These are summarised in Table 15, along with the development response.

²⁰ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

²¹ <https://uk-air.defra.gov.uk/pm25targets/planning>.

Table 15 Interim Planning Guidance Questions

Question	Response
How has exposure to PM_{2.5} been considered when selecting the development site? Factors to consider include: • Site proximity to people (particularly large populations and/or vulnerable groups, e.g. schools, hospitals, care homes, areas of deprivation) and the impact of the development on these • Site proximity to pollution sources and the impact of these on users of the development • Exposure and emissions during both construction and in-use	The site is located approximately 2km south of the centre of Bury, in the vicinity of residential and commercial properties. As such, the scheme is in close proximity to a large population. However, impacts at all locations are predicted to be not significant. This is supported by the assessment results summarised in Section 5.0 and 6.2 The development comprises floor space which will provide ancillary provision, including a gym and kitchen, for the consented JD office Campus. These site uses are not considered sensitive to long-term pollutant exposure As outlined in Table 14, a number of mitigation measures will be used throughout the construction phase in order to reduce fugitive dust emissions as far as practicable. This will control potential exposure at off-site locations
What actions and/or mitigations have been considered to reduce PM_{2.5} exposure for development users and nearby receptors and to reduce emissions of PM_{2.5} and its precursors? Factors to consider include: • Site layout • The development's design • Technology used in the construction or installed for use in the development • Construction and future use of the development	In order to reduce emissions of PM_{2.5} with associated impacts at nearby receptors and on site, the following measures have been included within the scheme: • Provision of Provision of Electric Vehicle (EV) charging points to encourage the uptake of low emission vehicles • Provision of secure cycle storage to encourage the use of sustainable transport modes • The client operates a minibus service to the site to reduce the amount of staff travelling in single occupancy cars • Photovoltaics (PV) will be installed on the roof of building to help provide electricity and hot water to the scheme Further to the above, in order to reduce emissions during the construction phase, a number of mitigation measures will be used to minimise dust generation from associated activities. These are outlined in Table 14

6.3.2 Based on the responses provided in Table 15 and the results of the assessment, it is considered that the development has identified key sources of air pollution and taken appropriate action to minimise emissions of PM_{2.5}.


7.0 CONCLUSION

- 7.1.1 Redmore Environmental Ltd was commissioned by JD Sports Fashion PLC to undertake an Air Quality Assessment in support of a mixed-use development at Hollins Brook Way, Unsworth, Bury.
- 7.1.2 The proposals have the potential to cause air quality impacts as a result of fugitive dust emissions during construction and road traffic exhaust emissions associated with vehicles travelling to and from the site during operation. As such, an Air Quality Assessment was undertaken to determine baseline conditions, consider site suitability for the proposed end-use and assess potential effects as a result of the scheme.
- 7.1.3 During the construction phase of the development there is the potential for air quality impacts from fugitive dust emissions from the site. These were assessed in accordance with the IAQM methodology and site specific dust control measures identified based on the results. Potential residual impacts from dust generated by earthworks, construction and trackout activities following implementation of the relevant mitigation was predicted to be **not significant**.
- 7.1.4 Potential impacts during the operational phase of the proposed development may occur due to road traffic exhaust emissions associated with vehicles travelling to and from the site. These were assessed against the screening criteria provided within the IAQM guidance. Due to the nature of the development, road traffic exhaust impacts were predicted to be **not significant**.
- 7.1.5 Based on the assessment results, air quality factors are not considered a constraint to planning consent for the development.

8.0 **ABBREVIATIONS**

AADT	Annual Average Daily Traffic
AQLV	Air Quality Limit Value
AQMA	Air Quality Management Area
AQO	Air Quality Objective
AQS	Air Quality Strategy
ASR	Annual Status Report
BC	Bury Council
CAP	Clean Air Plan
DEFRA	Department for Environment, Food and Rural Affairs
GMCA	Greater Manchester Combined Authority
HDV	Heavy Duty Vehicle
IAQM	Institute of Air Quality Management
LA	Local Authority
LAQM	Local Air Quality Management
LDV	Light Duty Vehicle
NGR	National Grid Reference
NO ₂	Nitrogen dioxide
NPPF	National Planning Policy Framework
NPPG	National Planning Policy Guidance
PfEP	Places for Everyone Plan
PM ₁₀	Particulate matter with an aerodynamic diameter of less than 10µm
PM _{2.5}	Particulate matter with an aerodynamic diameter of less than 2.5µm
TfGM	Transport for Greater Manchester
UDP	Unitary Development Plan

Figures



Legend



Title

Figure 1 - Site Location Plan

Project

Air Quality Assessment
Hollins Brook Way, Unsworth

Project Reference

9943


Client

JD Sports Fashion PLC

Contains Ordnance Survey Data
© Crown Copyright and Database Act 2023



www.red-env.co.uk | 0161 7060075



Legend

 Site Boundary

 Monitor

Title
Figure 2 - Monitoring Locations

Project
Air Quality Assessment
Hollins Brook Way, Unsworth

Project Reference
9943

Client
JD Sports Fashion PLC


Contains Ordnance Survey Data
© Crown Copyright and Database Act 2023



www.red-env.co.uk | 0161 7060075



Legend



Title

Figure 3 - Ecological Designation

Project

Air Quality Assessment
Hollins Brook Way, Unsworth

Project Reference

9943

Client

JD Sports Fashion PLC

Contains Ordnance Survey Data
© Crown Copyright and Database Act 2023



www.red-env.co.uk | 0161 7060075

Appendix 1 - Curricula Vitae

KEY EXPERIENCE:

Claire is a Director with specialist experience in the air quality sector

Her key capabilities include:

- Production and management of Air Quality, Dust and Odour Assessments for a wide range of clients from the residential, retail, commercial, leisure and industrial and infrastructure sectors.
- Detailed dispersion modelling of road vehicle and industrial emissions using ADMS-Roads, ADMS-6 and AERMOD. Studies have included impact assessment of ground level pollutant and odour concentrations and assessment of suitability of development sites for proposed end-use.
- Project management and co-ordination of Environmental Impact Assessments and scoping reports for developments throughout the UK.
- Assessment of fugitive dust impacts from a range of waste and industrial developments.
- Co-ordination and management of large-scale multi-disciplinary projects and submissions.
- Undertaken and overseeing pollutant monitoring campaigns.
- Provision of expert advice and attendance at DCO examination process.

SELECT PROJECTS SUMMARY:

Residential and Educational

Air Quality Assessments for a large number of proposed residential and educational developments across the UK. The assessments included consideration of construction phase dust emissions and mitigation was recommended to minimise fugitive dust emissions accordingly. The suitability of the sites for the proposed residential and educational uses was also assessed. The assessment utilised a range of assessment tools including relevant screening criteria, air dispersion modelling using ADMS-Roads, local air quality monitoring and Defra published assessment tools. Where required for sites in London, Air Quality Neutral assessments were also undertaken utilised the Greater London Authority guidance.

Air Quality Monitoring

Air Quality Assessments and overseeing air quality monitoring campaigns for a number of sites within Birmingham. Air dispersion modelling was undertaken and air quality monitoring utilising NO₂ diffusion tubes was carried out for use in verification of the dispersion model. Mitigation was recommended where appropriate to reduced the exposure of future uses of the sites to elevated pollutant concentrations.

Odour Assessments

Undertaken to support developments in the UK, including consideration of the impact of existing odour sources on proposed developments or to assess proposed odour releases. A combination of field odour surveys, risk assessments and detailed dispersion modelling were undertaken, with mitigation measures recommended where required.

Commercial and Retail

Foodstores across the UK - Air quality assessments for a number of proposed foodstores across the UK. Consideration was given to construction phase dust emissions and vehicle emissions generated by the foodstore operations. Relevant screening criteria and detailed air dispersion modelling were utilised in the assessment. Mitigation was recommended as required to minimise construction phase dust emissions.

Commercial development,

Workshop - Air quality assessment and input into the EIA for a proposed large scale commercial development near Workshop. Assessments of construction phase dust and operational phase road traffic emissions were undertaken and consideration was given to both human and ecological receptors.

Industrial and Infrastructure

Greater Manchester Waste PFI

Contract - Air Quality and Odour Assessments were undertaken as part of the Planning Applications and Environmental Permit applications for a number of proposed waste facilities in Greater Manchester.

Energy from Waste Development,

Scotland - Air Quality Assessment and coordination of the EIA and Environmental Permit Application for a proposed Energy from Waste development in Scotland. Considered industrial emissions from flue stacks as well as additional road traffic movements generated by the development

Strategic Rail Freight Interchange,

Hinckley - oversaw the Air Quality Assessment for the proposed Rail Freight Interchange and acted as expert witness as part of the Development Consent Order (DCO) examination process.

KEY EXPERIENCE:

Lauren is an Associate with specialist experience in the air quality sector. Her key capabilities include:

- Undertaking and managing a variety of air quality projects in a range of sectors including residential, student accommodation, educational, commercial and industrial projects
- Detailed dispersion modelling of road vehicle and industrial emissions using ADMS-Roads and ADMS-6. Studies have included impact assessment of ground level pollutant and odour concentrations and assessment of suitability of development sites for proposed end-use.
- Project management and co-ordination of Environmental Impact Assessments and scoping reports for developments throughout the UK.
- Co-ordination and management of multi-disciplinary projects and submissions.
- Assessment of fugitive dust impacts from a range of mineral extraction developments.
- Production of air quality mitigation strategies specifically tailored to address issues at individual sites.
- Active STEM Ambassador role, working with local schools to educate about air quality.

SELECT PROJECTS SUMMARY:

Norton Lodge, Malton

An ES Chapter and technical appendix were supplied to support this EIA development. The development comprised a new link road and therefore required multiple assessment scenarios. The Chapter also looked at impacts at ecological designations, impacts with an AQMA, odour from neighbouring facilities and impacts on proposed receptors. The AQMA in Malton was a particular concern for the council. The overall impact was considered to be not significant.

Yorkshire Post Phase 2, Leeds

An Air Quality Assessment to support each of the three proposed towers which form part of the Yorkshire Post Phase 2. These high-rise buildings were proposed for student accommodation and commercial uses. In addition to following LAQM.TG(22) and EPUK&IAQM guidance, the West Yorkshire Low Emissions Strategy (WYLES) Air Quality & Emissions Technical Planning Guidance was followed. Due to the 'Major' development classification in line with the WYLES guidance, damage costs for each tower were calculated. Mitigation measures were suggested. The energy strategy for the development was for a connection to the Leeds PIPES local heating district network.. The scheme was approved.

Old Hall Street, Liverpool

An Air Quality Assessment to support a student accommodation development. The scheme is 'car free' and trips generated dispersed to below the threshold once off Old Hall Street. The Site was considered suitable for residential use.

Viadux Phase 2, Manchester

Environmental Impact Assessment to support a high-rise residential led scheme in the city centre. The assessment included both operational and construction phase impacts. Impacts with both phases were considered to be 'not significant'. Additionally, in line with Manchester City Council Air Quality Guidance a Damage Cost calculation was included to ensure that sufficient mitigation was included to reduce air quality impacts as much as possible.

Plot 9b, First Street, Manchester

An ES Chapter to support the EIA development on land off First Street. The assessment included operational and construction phase impacts, in addition to modelling to ensure site suitability. Additionally, in line with Manchester City Council Air Quality Guidance a Damage Cost calculation was included to ensure that sufficient mitigation was included to reduce air quality impacts as much as possible. This included improving footpaths so that the site linked to other Plots within the wider First Street development. The Chapter concluded that impacts were considered not significant.

Winwick Road, Warrington

Air Quality Assessment for the proposed B2/B8 development in Warrington. Changes in pollution levels were considered at sensitive receptors as a result of trips generated and their distribution across the local area. Results of the dispersion modelling study indicated air quality impacts as a result of the scheme were not significant.