



SHEET ONE

SHEET TWO

Plant Schedule					
Trees					
Species		Height	Girth	Specification	Pot Size
Acer campestre		350-425cm	12-14cm	Heavy Standard	3x3B
Acer grimaldi		350-425cm	12-14cm	Heavy Standard	3x3B
Betula pendula		350-425cm	12-14cm	Heavy Standard	3x3RB
Malus tschonoskii		350-425cm	12-14cm	Heavy Standard	3x3B
Prunus avium		350-425cm	12-14cm	Heavy Standard	3x3B
Sorbus aria		350-425cm	12-14cm	Heavy Standard	3x3B
Sorbus aucup.	'Shoenswater Seeding'	350-425cm	12-14cm	Heavy Standard	3x3B

Shrubs	Species	Specification	Height	Pot Size	Density
Aucuba japonica 'Crotonifolia'	60-80cm	15L	3m		
Cyrtus scoparius 'Cornish Cream'	40-60cm	5L	4m		
Cotoneaster dammeri	30-40cm	3L	6m		
Chysoya ternata 'Sundance 9'	30-40cm	3L	4m		
Calluna vulgaris 'Gold Haze'	30-40cm	2L	10m		
Euonymus alatus 'Compactus'	30-40cm	3L	3m		
Escallonia 'Donard Seedling'	60-80cm	10L	3m		
Euonymus fortunei 'Emerald 'n' Gold'	30-40cm	5L	4m		
Euonymus fortunei 'Silver Queen'	30-40cm	5L	6m		
Hebe 'Autumn Glory'	30-40cm	3L	6m		
Hypericum 'Hidcote'	60-80cm	10L	3m		
Hypericum x roseostictum 'Tricolor'	30-40cm	3L	6m		
Lavandula angustifolia 'Vera'	30-40cm	5L	4m		
Mahonia aquifolium 'Apoll'	30-40cm	3L	6m		
Potentilla fruticosa 'Red Ace'	30-40cm	5L	6m		
Philadelphus 'Franklin D. Roosevelt'	60-80cm	10L	3m		
Sorbus aucup.	30-40cm	5L	6m		
Senecio 'Sunshine'	40-60cm	5L	6m		
Viburnum davidii	30-40cm	3L	6m		

NATIVE SHRUB MIX	Specification	Height	Percentage	Contribution	Density
Corylus avellana	Transplant 1+1	Double staggered row	60-80cm	20%	11m ²
Crataegus monogyna	Transplant 1+1	Double staggered row	60-80cm	30%	11m ²
Malus tschonoskii	Transplant 1+1	Double staggered row	60-80cm	30%	11m ²
Prunus spinosa	Transplant 1+1	Double staggered row	60-80cm	20%	11m ²

Hedges	Species	Specification	Height	Girth	Pot Size	Density
Buxus sempervirens	Single row	30-40cm	SL	4m		
Hebe 'Carl Teschner'	Single row	25-30cm	SL	6m		
Prunus laurocerasus 'Rotundifolia'	Single row	60-80cm	10L	4m		

GRASS SEED - To be sown at a rate of 50g/m².
A22 Hard Wearing, Low Maintenance. Available from Germinall GB. Tel: 01522 868714 (or similar approved)

SPECIFICATION
GROUND PREPARATION - GENERAL NOTES

CLIENTS/EXCAVATIONS
TRENCHES

General: Do not cut outside within preconstruction period.

Excavation in protected area:

Method: By hand.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

Delivery and storage: Break up to full depth.

Turf: Laid, aerated and break up to full depth.

Grading: 100 mm.

Backfill: As soon as possible or temporarily fill with polyethylene sheet to reduce evaporation.

Outside protected area: One side of road exceeding 25 mm and do not cut without approval.

Cutting: Make clean smooth cuts with no ragged edges.

Backfill: As dug material, enriched with phosphate fertiliser.

Ground Preparation: Compact and/or place fill to required profiles and levels.

Light and non-erosive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 100 mm.

STiff clay and cohesive subsoils: When ground conditions are reasonably dry, loosen thoroughly to a depth of 400 mm.

Rock and chalk subsoils: Lightly scarify to promote free drainage.

Stones: Immediately before spreading, remove stones larger than 50 mm.

Remove drainage, contaminants and debris and remove rubble.

Standard: In accordance with BS 4242.

Grading and cultivation: Category B.

Hard ground: Break up thoroughly.

Areas covered with turf or thick sward: Plough or dig over to full depth of soil.

Fallen sward (mossy) Not required.

Weed control: At appropriate times treat with a suitable translocated non-selective herbicide.

Imported topsoil: To BS 3602.

Quantity: Provide as necessary to make up any deficiency of topsoil existing on site and to complete the work.

Standard: To BS 3602.

Classification: Multipurpose.

Source: Contractor's choice.

Product reference: Contractor's choice.

CULTIVATION: Corrected topsoil: Break up to full depth.

</